

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 November 2005 (03.11.2005)

PCT

(10) International Publication Number
WO 2005/103914 A1

(51) International Patent Classification⁷: **G06F 13/00**, 3/12

(21) International Application Number:
PCT/JP2005/007282

(22) International Filing Date: 8 April 2005 (08.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-123443 19 April 2004 (19.04.2004) JP

(71) Applicant (for all designated States except US): **CANON KABUSHIKI KAISHA** [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **OOMURA, Hiroshi** [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP).


(74) Agent: **OHTSUKA, Yasunori**; 7TH FL., SHUWA KIOICHO PARK BLDG., 3-6, KIOICHO, CHIYODA-KU, TOKYO, 1020094 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: NETWORK DEVICE MANAGEMENT APPARATUS AND ITS CONTROL METHOD, COMPUTER PROGRAM AND COMPUTER-READABLE STORAGE MEDIUM



(57) Abstract: The present invention makes other devices on a network recognize a device that does not support the network compatible Plug and Play function as a device that supports the network compatible Plug and Play function, and makes that device serve as the device with the function. To this end, a proxy server searches for a printer which is present on the network and does not support any network compatible Plug and Play function, and registers information used to specify the found printer in a hard disk via a memory controller. Upon registration, the proxy server generates network compatible Plug and Play DeviceDescription so as to behave as if it were a network compatible Plug and Play device. Upon reception of a network compatible Plug and Play search message from the network, the proxy server transmits the generated DeviceDescription as a response message to indicate a UPnP device in place of the printer that does not support the network compatible Plug and Play device. Upon reception of a print job addressed to the registered printer, the proxy server converts the print job to a protocol for that printer, and transmits the converted job data to the printer.



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*